


AD-A134 875 THEORETICAL ASPECTS OF LASER-INDUCED PERIODIC SURFACE  
STRUCTURE FORMATION(U) ROCHESTER UNIV NY DEPT OF  
CHEMISTRY M HUTCHINSON ET AL. NOV 83

1/1

UNCLASSIFIED UROCHESTER/DC/83-TR-43 N00014-80-C-0472 F/G 7/4 NL



END  
DATE  
FILMED  
12-83  
DTIC



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS - 1963 - A

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

(12)

AD-A134875

DTIC FILE COPY

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER UROCHESTER/DC/83/TR-43	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Theoretical Aspects of Laser-Induced Periodic Surface Structure Formation		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Michael Hutchinson, Ki-Tung Lee, William C. Murphy, A. C. Beri and Thomas F. George		8. CONTRACT OR GRANT NUMBER(s) N00014-80-C-0472
9. PERFORMING ORGANIZATION NAME AND ADDRESS Department of Chemistry University of Rochester Rochester, New York 14627		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 056-749
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Chemistry Program Code 472 Arlington, Virginia 22217		12. REPORT DATE November 1983
		13. NUMBER OF PAGES 8
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  This document has been approved for public release and sale; its distribution is unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)  DTIC ELECTE NOV 22 1983		
18. SUPPLEMENTARY NOTES  Prepared for publication in <u>Laser-Controlled Chemical Processing of Surfaces</u> , ed. by A. W. Johnson and D. J. Ehrlich (Elsevier, New York)		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) PERIODIC SURFACE STRUCTURE FORMATION LASER-INDUCED THEORETICAL STUDY MAXWELL'S EQUATIONS SMOOTH SURFACE GRATINGS ROUGH SURFACE GRATINGS MULTILAYERED GRATINGS SQUARE-WELL SILVER GRATING		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Laser-induced periodic pattern formation has been observed on a variety of substances. In particular, low-power lasers have been used to deposit a pattern on a metal surface. For a relatively smooth surface grating, this pattern can be explained in terms of a perturbative solution of Maxwell's equations. However, as the surface grating is enhanced by this initial deposition, the perturbation solution breaks down. An alternate non-perturbative solution of Maxwell's equations for such rough surfaces is considered here. Moreover, other possible mechanisms that may assist pattern formation are discussed, such as field-enhanced evaporation and surface migration.		

DD FORM 1 JAN 73 1473

83 11 22 088classified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

OFFICE OF NAVAL RESEARCH

Contract N00014-80-C-0472

Task No. NR 056-749

TECHNICAL REPORT No. 43

Theoretical Aspects of Laser-Induced  
Periodic Surface Structure Formation

by

Michael Hutchinson, Ki-Tung Lee,  
William C. Murphy, A. C. Beri and Thomas F. George

Prepared for Publication

in

Laser-Controlled Chemical Processing of Surfaces, ed. by  
A. W. Johnson and D. J. Ehrlich (Elsevier, New York)

Department of Chemistry  
University of Rochester  
Rochester, New York 14627

November 1983

Reproduction in whole or in part is permitted for any  
purpose of the United States Government.

This document has been approved for public release  
and sale; its distribution is unlimited.

820 35 11 88

THEORETICAL ASPECTS OF LASER-INDUCED  
PERIODIC SURFACE STRUCTURE FORMATION

MICHAEL HUTCHINSON, KI-TUNG LEE, WILLIAM C. MURPHY,  
A. C. BERI AND THOMAS F. GEORGE  
Department of Chemistry, University of Rochester  
Rochester, New York 14627

ABSTRACT

Laser-induced periodic pattern formation has been observed on a variety of substances. In particular, low-power lasers have been used to deposit a pattern on a metal surface. For a relatively smooth surface grating, this pattern can be explained in terms of a perturbative solution of Maxwell's equations. However, as the surface grating is enhanced by this initial deposition, the perturbation solution breaks down. An alternate non-perturbative solution of Maxwell's equations for such rough surfaces is considered here. Moreover, other possible mechanisms that may assist pattern formation are discussed, such as field-enhanced evaporation and surface migration.

After reduction to 75% scale rectangle will be 12.1 x 12.2 cm.

INTRODUCTION

Over the past several years, a number of researchers [1-17] have observed periodic patterns developing on the surfaces of solids that were exposed to laser radiation. These patterns have been seen on various metals, insulators, and both doped and pure semiconductors. Most of these experiments were carried out with Nd:YAG or Nd:glass lasers tuned to wavelengths between 1.0  $\mu\text{m}$  and 10.0  $\mu\text{m}$ . To obtain these patterns, laser power densities of between 10 MW/cm<sup>2</sup> and 1 GW/cm<sup>2</sup> were employed. Above this range, surface melting would occur, while below this level, no discernible surface pattern was observed.

This laser-induced periodic surface structure has several characteristics. First, the surface pattern consists of a number of parallel grooves running perpendicular to the E field of the incident laser. Second, Oron and Sorensen [8] demonstrated that the underlying surface lattice has no effect on the shape of the laser-induced surface structure. On the other hand, Isenor [6] has shown that the existence of scratches on the surface can have a significant effect on the final surface structure. In fact, if the surface is randomly scratched, no periodic surface structure will form. Both Brueck and Ehrlich [12] and van Driel and his colleagues [13] have also observed the development of a weaker secondary pattern parallel to the incident E field. With this secondary structure, the surface takes on a scalloped appearance. Finally, these surface patterns produce large drops in the reflectivity of several metals [3-4].

Most of the work so far has considered laser-induced periodic structures on surfaces that already had a certain composition. Needless to say, this necessitates large laser power densities (greater than 10 MW/cm<sup>2</sup>) in order to provide sufficient energy for the surface atoms to rearrange. However, Brueck and Ehrlich [12] showed that only a modest amount of laser power (less than 10 W/cm<sup>2</sup>) is needed to establish the periodic surface structure when the constituent atoms are deposited from the gas phase. In particular, they showed that Cd, Zn and Al in organometallic compounds could be photochemically deposited on Si or SiO<sub>2</sub> substrates in ordered arrays.



Accession  
NTIS GRANT  
DTIC TAB  
Unannounced  
Justification

Distribution/

Availability Codes

Avail and/or  
Special

A-1

To understand these observations and resolve any difficulties, one must consider how this laser-induced periodic surface structure is produced. There have been three attempts to explain these effects. First, since many metals have a plasma frequency around the frequency of the incident laser radiation, surface plasmons will be excited [11-12]. These plasmons will couple with the electromagnetic field to form a surface polariton. Since this polariton produces maxima and minima in the  $\vec{E}$  field of the surface, the surface atoms will rearrange themselves to minimize their energy in this  $\vec{E}$  field. Second, Maracas et al [7] have observed that the periodic surface structure can be considered a standing wave. This wave would have a velocity very close to that of a longitudinal acoustic phonon of the substrate. Thus, the surface pattern may well be a phonon excited by the laser that was "frozen" in place by the cooling of the lattice. Finally, van Driel and his associates [15] have proposed an extensive theory based on the small inhomogeneities that exist in the surface layer. This initial surface roughness will interact with the incident laser beam to produce a dipole moment in the surface layer (a "radiation remnant"). The field generated by this dipole layer can interfere with the refracted beam in the substrate below the surface. This interference will lead to inhomogeneous energy absorption and thus the redistribution of the surface atoms.

In the following section, the theory of the surface enhanced  $\vec{E}$  field produced by relatively smooth surfaces and the resultant pattern formation will be viewed. The inapplicability of this approach to rough gratings will be demonstrated. To overcome this limitation, a non-perturbative solution of Maxwell's equations will be discussed. Finally, our results will be presented along with suggested improvements.

#### THEORY OF SMOOTH GRATINGS

Incident radiation converted to surface plasmon excitations via surface roughness has been investigated extensively in the past decade [18]. The classical method of Rayleigh [19] has often been used to solve the problem of weak scattering [20]. Brueck and Ehrlich [12] also adapted this formalism to describe the phenomena of laser-induced pattern formation. Here, we will briefly outline the theory of Brueck and Ehrlich and discuss its validation and limitation.

Let a light wave of frequency  $\omega$  represented by an electric field

$$\vec{E}_{\text{inc}}(\vec{r}, t) = E_i e^{-ik_0 z} e^{-i\omega t} \quad (1)$$

be incident on the metal surface at a normal angle, on the xz-plane. If we express the surface roughness in terms of a Fourier expansion,

$$z = \xi(x, y) = \sum_{\vec{g}} u_{\vec{g}} e^{i\vec{g} \cdot \vec{r}_{\parallel}} \quad , \quad \vec{g} = (g_x, g_y), \quad \vec{r}_{\parallel} = (x, y), \quad (2)$$

and assume that each amplitude  $u_{\vec{g}}$  is small compared to the wavelength of the incident light, then taking the dielectric function as a step function,

$$\epsilon(\omega, \vec{r}) = \epsilon(\omega) \theta(z - \xi) + \theta(\xi - z), \quad (3)$$

we can write down the solutions of the Maxwell's equations separately for the two media. In particular, for  $g^2 > \omega^2/c^2$  and  $z > \xi$ , we have

$$\vec{E} = \vec{E}_i e^{-ik_0 z} + \vec{E}_r e^{ik_0 z} + \vec{E}_{\text{sp}} e^{i\vec{g} \cdot \vec{r}_{\parallel}} e^{-k_g z}, \quad (4)$$

where  $k_g^2 = g^2 - \omega^2/c^2$ . By imposing the boundary conditions, i.e., the local

tangential components of the electric and magnetic fields have to be continuous across the actual surface  $z = \xi(x, y)$ , we can express the reflected and surface plasmon fields,  $\vec{E}_r$  and  $\vec{E}_{sp}$  respectively, in terms of  $\vec{E}_i$  by writing

$$e^{ik_0\xi} \approx (1 + ik_0\xi) \quad (5)$$

and assuming  $g\xi \ll 1$  in the continuity equations. If we consider only the p-wave scattering, i.e., the light polarized in the x-direction, the expression of Brueck and Ehrlich for  $\vec{E}_{sp}$  can then be easily obtained. If we assume a linear relationship between the film growth rate and the local intensity,

$$\frac{dT}{dt} \propto I(x) = |\vec{E} \cdot \vec{E}|, \quad (6)$$

then the suggested equation of the grating depth  $u_z$  is obtained by assuming a spatial profile of  $T(x) = T_0 + u \cos(gx)$ , and neglecting the  $|\vec{E}_{sp}|^2$  term.

The foregoing theory was developed under the assumption that the surface roughness is small,  $g\xi \ll 1$ . However, as more metal is deposited, the roughness increases. In the perturbative theory of Brueck and Ehrlich,  $\vec{E}_{sp}$  is proportional to the roughness  $u$ . Therefore, the first consequence of increased roughness is that  $|\vec{E}_{sp}|^2$  can no longer be neglected. This point may already be reached when the grating is only a few layers deep. Moreover, the damping of  $\vec{E}_{sp}$  can no longer be measured from the mean surface. An increase in roughness can lead to sufficient enhancement of  $\vec{E}_{sp}$  that localized evaporation of metal atoms could play an important role. Transfer of large amounts of energy to the metal-carbon bond, such as in the deposition of Cd on Si due to the dissociation of gaseous  $\text{Cd}(\text{CH}_3)_2$ , may also induce sufficient translational motion along the surface so that adsorption does not occur at the dissociation site. Such dissociation under several possibly physisorbed organometallic layers could lead to trapping of the organic radical in the vicinity of the surface. This "cage" effect could lead to the reformation of the organic metal bond. Finally, the effect of surface roughness on the dielectric function might be important. Such increases of surface area could substantially alter the magnitude of this function, which in turn could enhance the rate of pattern formation.

#### GENERALIZATION TO ROUGH GRATINGS

The foregoing considerations lead us to conclude that an explanation of deep pattern formation requires a non-perturbative treatment of plasmon formation, and at the present time a numerical solution of Maxwell's equations seems inevitable. Recently [21] there has appeared a solution of the problem of a square-well metallic grating in an applied electromagnetic field (FIG. 1b). Such a solution is restricted to explaining the most qualitative features of sinusoidal grating formation. We have established a general formulation of the problem which is capable in principle of handling gratings of any shape or depth.

In the H polarization, Maxwell's equations can be written as [22]

$$-\frac{\partial^2 H_y}{\partial z^2} + \frac{\partial^2 H_y}{\partial x^2} + \epsilon(x)k_0^2 H_y = \frac{\partial H_y}{\partial x} \frac{\partial}{\partial x} [\epsilon n \epsilon(x)], \quad (7)$$

where  $H_y$  is the component of the magnetic field  $H$  in the direction perpendicular to the lattice vector of the grating (FIG. 1). For square-well gratings,  $H_y$  is separable,



$$H_y(x, y) = Z(z) X(x), \quad (8)$$

and Eq. (7) can be written as two coupled first-order differential equations:

$$\frac{\partial Z^2}{\partial z^2} = \Lambda^2 Z \quad (9a)$$

$$\frac{\partial^2 X}{\partial x^2} - \frac{\partial}{\partial x} [\epsilon n \epsilon(x)] \frac{\partial X}{\partial x} + [\epsilon(x) k_0^2 - \Lambda^2] X = 0. \quad (9b)$$

When the applied radiation is incident normal to the grating, it is found that  $\Lambda$  is the solution of the equation

$$1 - \cos(\beta d/2) \cos(\alpha d/2) + 1/2(\epsilon \alpha / \beta + \beta / (\epsilon \alpha)) \sin(\beta d/2) \sin(\alpha d/2) = 0, \quad (10)$$

where  $d$  is the period of the grating,  $\epsilon$  is the dielectric constant of the grating,  $\alpha = (k_0^2 - \Lambda^2)^{1/2}$  and  $\beta = (\epsilon k_0^2 - \Lambda^2)^{1/2}$ .

The problem to be considered (FIG. 1c) is that of a multilayered grating. In each layer the grating is periodic and the general solution to Eq. (9) for the  $n$ -th layer may be written as

$$\psi_n^{II} = \sum_{\ell} X_{n\ell}(x) [A_{n\ell} e^{i\Lambda_{n\ell} z} + B_{n\ell} e^{-i\Lambda_{n\ell} z}], \quad (11)$$

where the coefficients  $A$  and  $B$  are to be determined by the boundary conditions between layers, and  $\Lambda_{n\ell}$  is the  $\ell$ -th solution to Eq. (10) for the  $n$ -th layer. By applying the boundary condition of continuity of  $H_y$  and  $\frac{\partial}{\partial z}$  between layers, we can establish the recursion relations for  $A$  and  $B$ ,

$$\vec{A}_n = E_{n,n-1} \vec{A}_{n-1} + F_{n,n-1} \vec{B}_{n-1} \quad (12a)$$

$$\vec{B}_n = C_{n,n-1} \vec{A}_{n-1} + D_{n,n-1} \vec{B}_{n-1}, \quad (12b)$$

where the matrices  $C, D, E, F$  are determined by the periodic structure of each layer. Furthermore, we can establish boundary conditions between the top two layers and the two lowest layers. In the topmost (infinite) layer, the eigensolution is written as [21]

$$\psi^I = e^{-ik_0 z} + \sum_{n=-\infty}^{\infty} R_n e^{ik_0 [\gamma_n x + (1-\gamma_n^2)^{1/2} z]}. \quad (13)$$

In the lowest (infinite layer) we have

$$\psi^{III} = \sum_{n=-\infty}^{\infty} T_n e^{ik_0 [\gamma_n x - (\epsilon - \gamma_n^2)^{1/2} z]} \quad (14)$$

where  $\gamma_n = \frac{n\lambda}{d}$ .

It is now possible to establish

$$\vec{A}_1 = a\vec{D} + b\vec{R} \quad (15a)$$

$$\vec{B}_1 = b\vec{D} + a\vec{R}, \quad (15b)$$

where  $\vec{D}$  is a unit vector. In addition,



$$\vec{A}_N = L\vec{B}_N, \quad (16)$$

where N labels the penultimate (finite) layer, and the matrix L is determined by the parameters which characterize that layer. However, by applying the recursion relations of Eq. (12), it is possible to establish

$$\vec{A}_N = J_1\vec{D} + J_2\vec{R} \quad (17a)$$

$$\vec{B}_N = K_1\vec{D} + K_2\vec{R} \quad (17b)$$

Rearranging (16) and (17) gives

$$\vec{R} = (J_2 - LK_2)^{-1} (LK_1 - J_1)\vec{D}, \quad (18)$$

and by employing Eq. (12) once more we arrive finally at a matrix equation for the vectors  $\vec{A}_M$  and  $\vec{B}_M$ ,

$$\begin{pmatrix} \vec{A}_M \\ \vec{B}_M \end{pmatrix} = \prod_{n=2}^M \begin{pmatrix} E_{n,n-1} & F_{n,n-1} \\ C_{n,n-1} & D_{n,n-1} \end{pmatrix} \begin{pmatrix} a & b \\ b & a \end{pmatrix} \begin{pmatrix} \vec{D} \\ \vec{R} \end{pmatrix}. \quad (19)$$

## RESULTS AND DISCUSSION

We have made a preliminary calculation for a square-well silver grating. The field intensity  $|\vec{E}(z,x)|^2$  is averaged over x at each of two values of z ( $z = 0$  and  $z = -h$ ), and the ratio  $R = |E(z = -h)|^2 / |E(z = 0)|^2$  is plotted as a function of the well-depth (roughness parameter) h (FIG. 2). R is thus the ratio of intensity in the "peak" region of the grating to that in the "well" region. For very shallow gratings ( $h < 0.5$  nm), or about two monolayers) it is seen that  $|E(z=0)|^2 > |E(z=-h)|^2$ , which supports the perturbation description of Brueck and Ehrlich. This would explain how a particular grating establishes itself out of the "noise" of microscopic roughness. It also explains why the establishment of such a grating for low-power lasers requires the photodissociation of an organometallic compound and does not occur in the presence of metal vapor alone. However, at a certain depth (around 0.5 nm)  $|E(z = -h)|^2$  begins to increase very rapidly. It seems here that the grating structure will only continue to reinforce itself by a mechanism other than photodeposition. Such a mechanism might be photo-evaporation of the grating itself, whereby the trough regions are "excavated" by the field. Finally, we note that as  $h \rightarrow \infty$ ,  $|E(z = -h)|^2 \rightarrow 0$ . This is consistent with an upper unit to the growth of the grating. Work is currently underway to determine whether these qualitative trends are consistent also with sinusoidal gratings.

## ACKNOWLEDGMENTS

This work was supported in part by the U.S. Army Research Office, the Office of Naval Research and the Air Force Office of Scientific Research (AFSC) under Grant No. AFOSR-82-0046. The United States Government is authorized to reproduce and distribute reprints for governmental purposes notwithstanding any copyright notation hereon. TFG acknowledges the Camille and Henry Dreyfus Foundation for a Teacher-Scholar Award (1975-84) and the John Simmon Guggenheim Memorial Foundation for a Fellowship (1983-84).

# REFERENCES

1. M. Birnbaum, J. Appl. Phys. 36, 3688 (1965).
2. D. C. Emmony, R. P. Howson and L. J. Willis, Appl. Phys. Lett. 23, 598 (1977).
3. T. E. Zavecz and M. A. Saifi, Appl. Phys. Lett. 26, 165 (1975).
4. J. C. Koo and R. E. Slusher, Appl. Phys. Lett. 28, 614 (1976).
5. N. R. Isenor, Appl. Phys. Lett. 31, 148 (1977).
6. H. J. Leamy, G. A. Rozgonyi, T. T. Sheng and G. K. Celler, Appl. Phys. Lett. 32, 535 (1978).
7. G. N. Maracas, G. L. Harris, C. A. Lee and R. A. McFarlane, Appl. Phys. Lett. 33, 453 (1978).
8. M. Oron and G. Sorensen, Appl. Phys. Lett. 35, 782 (1979).
9. A. K. Jain, V. N. Kulkarni, D. K. Sood and J. S. Uppal, J. Appl. Phys. 52, 4882 (1981).
10. P. A. Temple and M. J. Soileau, IEEE J. Quantum Electron. QE-17, 2067 (1981).
11. P. M. Fauchet and A. E. Siegman, Appl. Phys. Lett. 40, 1678 (1982).
12. S. R. J. Brueck and D. J. Ehrlich, Phys. Rev. Lett. 48, 1678 (1982).
13. J. F. Young, J. E. Sipe, J. S. Preston and H. M. van Driel, Appl. Phys. Lett. 41, 261 (1982).
14. H. M. van Driel, J. E. Sipe and J. F. Young, Phys. Rev. Lett. 49, 1955 (1982).
15. J. E. Sipe, J. F. Young, J. S. Preston and H. M. van Driel, Phys. Rev. B 27, 1141 (1983).
16. J. F. Young, J. S. Preston, H. M. van Driel and J. E. Sipe, Phys. Rev. B 27, 1155 (1983).
17. J. F. Young, J. S. Preston, J. E. Sipe and H. M. van Driel, Phys. Rev. B 27, 1424 (1983).
18. For a comprehensive review, see A. A. Maradudin, in Surface Polaritons, ed. by V. M. Agranovich and D. L. Mills (North-Holland, Amsterdam, 1982), pp. 405-510.
19. Lord Rayleigh, Philos. Mag. 14, 60 (1907); Proc. R. Soc. London, Ser. A 79, 399 (1907).
20. A. Marin, F. Toigo and V. Celli, Phys. Rev. B 11, 2777 (1974); S. S. Jha, J. R. Kirtley and J. C. Tsang, Phys. Rev. B 22, 3973 (1982).
21. P. Sheng, R. S. Stepheman and P. N. Sanda, Phys. Rev. B 26, 2907 (1982).
22. M. Born and E. Wolf, Principles of Optics (Pergamon, New York, 1975), Chapt. 1.




FIG. 1.

- (a) Sinusoidal grating. The hatched area represents the metal.
- (b) Square-well grating showing a separation into three layers, one of which is periodic in the x-direction, and two of which are uniform.
- (c) Generalization of the square-well grating in which there are three periodic layers.




FIG. 2. Log-log plot of the ratio  $R = \frac{|E(z=-h)|^2}{|E(z=0)|^2}$  against the grating depth  $h$ , for a silver grating with  $d = 1050$  nm and  $\lambda = 700$  nm. The horizontal line corresponds to  $R = 1$ . Above the line the intensity is greatest in the region of the well ( $z = -h$ ); below the line the intensity is greatest in the region of the peaks ( $z = 0$ ) of the grating. Clearly the latter condition pertains for very smooth gratings ( $h \rightarrow 0$ ) and also for very rough gratings ( $h \rightarrow \infty$ ).

TECHNICAL REPORT DISTRIBUTION LIST, GEN

	<u>No. Copies</u>		<u>No. Copies</u>
Office of Naval Research Attn: Code 413 800 North Quincy Street Arlington, Virginia 22217	2	Naval Ocean Systems Center Attn: Mr. Joe McCartney San Diego, California 92152	1
ONR Pasadena Detachment Attn: Dr. R. J. Marcus 1030 East Green Street Pasadena, California 91106	1	Naval Weapons Center Attn: Dr. A. B. Amster, Chemistry Division China Lake, California 93555	1
Commander, Naval Air Systems Command Attn: Code 310C (H. Rosenwasser) Department of the Navy Washington, D.C. 20360	1	Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko Port Hueneme, California 93401	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12	Dean William Tolles Naval Postgraduate School Monterey, California 93940	1
Dr. Fred Saalfeld Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375	1	Scientific Advisor Commandant of the Marine Corps (Code RD-1) Washington, D.C. 20380	1
U.S. Army Research Office Attn: CRD-AA-IP P. O. Box 12211 Research Triangle Park, N.C. 27709	1	Naval Ship Research and Development Center Attn: Dr. G. Bosmajian, Applied Chemistry Division Annapolis, Maryland 21401	1
Mr. Vincent Schaper DTNSRDC Code 2803 Annapolis, Maryland 21402	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 19112	1
Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1	Mr. A. M. Anzalone Administrative Librarian PLASTEC/ARRADCOM Bldg 3401 Dover, New Jersey 07801	1
Dr. David L. Nelson Chemistry Program Office of Naval Research 800 North Quincy Street Arlington, Virginia 22217	1		

TECHNICAL REPORT DISTRIBUTION LIST, 056

	<u>No.</u> <u>Copies</u>		<u>No.</u> <u>Copies</u>
Dr. G. A. Somorjai Department of Chemistry University of California Berkeley, California 94720	1	Dr. W. Kohn Department of Physics University of California (San Diego) La Jolla, California 92037	1
Dr. J. Murday Naval Research Laboratory Surface Chemistry Division (6170) 455 Overlook Avenue, S.W. Washington, D.C. 20375	1	Dr. R. L. Park Director, Center of Materials Research University of Maryland College Park, Maryland 20742	1
Dr. J. B. Hudson Materials Division Rensselaer Polytechnic Institute Troy, New York 12181	1	Dr. W. T. Peria Electrical Engineering Department University of Minnesota Minneapolis, Minnesota 55455	1
Dr. Theodore E. Madey Surface Chemistry Section Department of Commerce National Bureau of Standards Washington, D.C. 20234	1	Dr. Chia-wei Woo Department of Physics Northwestern University Evanston, Illinois 60201	1
Dr. J. M. White Department of Chemistry University of Texas Austin, Texas 78712	1	Dr. Robert M. Hexter Department of Chemistry University of Minnesota Minneapolis, Minnesota 55455	1
Dr. Keith H. Johnson Department of Metallurgy and Materials Science Massachusetts Institute of Technology Cambridge, Massachusetts 02139	1	Dr. R. P. Van Duyne Chemistry Department Northwestern University Evanston, Illinois 60201	1
Dr. J. E. Demuth IBM Corporation Thomas J. Watson Research Center P. O. Box 218 Yorktown Heights, New York 10598	1	Dr. S. Sibener Department of Chemistry James Franck Institute 5640 Ellis Avenue Chicago, Illinois 60637	1
Dr. C. P. Flynn Department of Physics University of Illinois Urbana, Illinois 61801	1	Dr. M. G. Lagally Department of Metallurgical and Mining Engineering University of Wisconsin Madison, Wisconsin 53706	1

TECHNICAL REPORT DISTRIBUTION LIST, 056

	<u>No. Copies</u>		<u>No. Copies</u>
Dr. Robert Gomer Department of Chemistry James Franck Institute 5640 Ellis Avenue Chicago, Illinois 60637	1	Dr. K. G. Spears Chemistry Department Northwestern University Evanston, Illinois 60201	1
Dr. R. G. Wallis Department of Physics University of California, Irvine Irvine, California 92664	1	Dr. R. W. Plummer University of Pennsylvania Department of Physics Philadelphia, Pennsylvania 19104	1
Dr. D. Ramaker Chemistry Department George Washington University Washington, D.C. 20052	1	Dr. E. Yeager Department of Chemistry Case Western Reserve University Cleveland, Ohio 41106	1
Dr. P. Hansma Physics Department University of California, Santa Barbara Santa Barbara, California 93106	1	Professor D. Hercules University of Pittsburgh Chemistry Department Pittsburgh, Pennsylvania 15260	1
Dr. J. C. Hemminger Chemistry Department University of California, Irvine Irvine, California 92717	1	Professor N. Winograd The Pennsylvania State University Department of Chemistry University Park, Pennsylvania 16802	1
Dr. Martin Fleischmann Department of Chemistry Southampton University Southampton SO9 5NH Hampshire, England	1	<del>Professor T. F. George The University of Rochester Chemistry Department Rochester, New York 14627</del>	<del>1</del>
Dr. G. Rubloff IBM Thomas J. Watson Research Center P. O. Box 218 Yorktown Heights, New York 10598	1	Professor Dudley R. Herschbach Harvard College Office for Research Contracts 1350 Massachusetts Avenue Cambridge, Massachusetts 02138	1
Dr. J. A. Gardner Department of Physics Oregon State University Corvallis, Oregon 97331	1	Professor Horia Metiu University of California, Santa Barbara Chemistry Department Santa Barbara, California 93106	1
Dr. G. D. Stein Mechanical Engineering Department Northwestern University Evanston, Illinois 60201	1	Professor A. Steckl Rensselaer Polytechnic Institute Department of Electrical and Systems Engineering Integrated Circuits Laboratories Troy, New York 12181	1

TECHNICAL REPORT DISTRIBUTION LIST, 056

	<u>No.</u> <u>Copies</u>	<u>No.</u> <u>Copies</u>
Dr. John T. Yates Department of Chemistry University of Pittsburgh Pittsburgh, Pennsylvania 15260	1	
Professor G. H. Morrison Department of Chemistry Cornell University Ithaca, New York 14853	1	
Captain Lee Myers AFOSR/NC Bolling AFB Washington, D.C. 20332	1	
Dr. David Squire Army Research Office P. O. Box 12211 Research Triangle Park, NC 27709	1	
Professor Ronald Hoffman Department of Chemistry Cornell University Ithaca, New York 14853	1	



**DAT  
FILM**